
Coaxial **SMA Fixed Attenuator**

50Ω 30dB 0.5W

Maximum Ratings

Operating Temperature	-45°C to 100°C			
Storage Temperature	-55°C to 100°C			
Permanent damage may occur if any of these limits are exceed				

Outline Drawing



Outline Dimensions (inch)

В	D	Е	wt
.410	1.43	.312	grams
10.41	36.32	7.92	10.0

Electrical Schematic

R3 <

-0

C

FEMALE

 \sim

R2

 $\leq R1$

C

MALE

0

DC to 6000 MHz

Features

- wideband coverage, DC to 6000 MHz
- rugged unibody construction
- off-the-shelf availability very low cost

Applications

- impedance matching
- signal level adjustment



VAT-30+

	CASE STYLE: FF704		
Connectors	Model	Price	Qty.
SMA	VAT-30+	\$13.95 ea.	(1-9)

+RoHS Compliant The +Suffix identifies RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications


Electrical Specifications


FREQ. RANGE (MHz)	ATTENUATION * (dB) Flatness **			VSWR (:1)			MAX. INPUT POWER		
		DC-3 GHz	3-5 GHz	5-6 GHz	DC-6 GHz	DC-3 GHz	3-5 GHz	5-6 GHz	(W)
f _L -f _U	Nom.	Тур.	Тур.	Тур.	Тур.	Тур. Мах.	Тур. Мах.	Тур.	
DC-6000	30±0.3	1.10	0.70	0.35	1.30	1.05 1.20	1.15 1.30	1.25	0.5

* Attenuation varies by 0.3 dB max. over temperature.

** Flatness= variation over band divided by 2.

Typical Performance Data Attenuation VSWR Frequency (MHz) (dB) (:1) 0.03 50.00 30.05 29.99 1.00 1.00 100.00 29.96 1.01 500.00 29.33 1.02 1000.00 28.79 1.04 2000.00 28.77 1 06 3000.00 29.08 1.08 4000.00 29.22 1.03 5000.00 28 72 1 03 6000.00 29.36 1.07





REV. G M129173

VAT-30+ LC/TD/CP/AM

130923 Page 1 of 1

A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document. B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement ins C. The parts covered by this specification document are subject to Mini-Circuit's standard limited warrantv and terms and conditions (collectively: "Standard Terms"): Purchasers of this performance Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions. The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuit's website at www.minicircuits.com/MCLStore/terms.jsp

Mini-Circuits